

Practitioner's Docket No. BGR-017PCT/US

CHAPTER II

#3/a

## Preliminary Classification:

Proposed Class:

Subclass:

NOTE: "All applicants are requested to include a preliminary classification on newly filed patent applications. The preliminary classification, preferably class and subclass designations, should be identified in the upper right-hand corner of the letter of transmittal accompanying the application papers, for example 'Proposed Class 2, subclass 129.'" M.P.E.P., § 601, 7th ed.

## AMENDMENT ACCOMPANYING NEW APPLICATION TRANSMITTAL

## (ENTRY INTO U.S. NATIONAL PHASE UNDER CHAPTER II)

INTERNATIONAL APPLICATION NO.	INTERNATIONAL FILING DATE	PRIORITY DATE CLAIMED
PCT/US00/40401	18 July 2000 (18.07.00)	21 July 1999 (21.07.99)
TITLE OF INVENTION		
Enhanced Crossflow Heat Transfer		
APPLICANT(S)		
Washington Group International, Inc.; LARSEN, Thomas L.; JAYASWAL, Umesh K.		
Box PCT		
Assistant Commissioner for Patents		
Washington D.C. 20231 U.S. Patent and Trademark Office		
ATTENTION: EO/US P.O. Box 2327		
Arlington, VA 22202		
Attention: EO/US		

**CERTIFICATION UNDER 37 C.F.R. § 1.10\***  
 (Express Mail label number is mandatory.)  
 (Express Mail certification is optional.)

I hereby certify that this Transmittal Letter and the papers indicated as being transmitted therewith is being deposited with the United States Postal Service on this date January 14, 2002 in an envelope as "Express Mail Post Office to Addressee" Mailing Label Number ET063376739US, addressed to the: Assistant Commissioner for Patents, Washington, D.C. 20231 U.S. Patent and Trademark Office, P.O. Box 2327, Arlington, VA 22202

Leslie R. Silverstein

(type or print name of person mailing paper)



Signature of person mailing paper

**WARNING:** Certificate of mailing (first class) or facsimile transmission procedures of 37 C.F.R. § 1.8 cannot be used to obtain a date of mailing or transmission for this correspondence.

**\*WARNING:** Each paper or fee filed by "Express Mail" must have the number of the "Express Mail" mailing label placed thereon prior to mailing. 37 C.F.R. § 1.10(b).

"Since the filing of correspondence under § 1.10 without the Express Mail mailing label thereon is an oversight that can be avoided by the exercise of reasonable care, requests for waiver of this requirement will not be granted on petition." Notice of Oct. 24, 1996, 60 Fed. Reg. 56,436, at 56,442.

(Transmittal Letter to the United States Elected Office (EO/US) [13-18]—page 1 of 8)

BGR-017PCT/US  
Preliminary Amendment

J. Heron  
#3 / Pre  
Amendment  
10/8/2002

PRELIMINARY AMENDMENT

For the purposes of proceeding with this U.S. national stage application under  
35 U.S.C. 371, please amend the claims of the above-identified PCT application as follows:

In the Claims

Cancel claims 1 - 38 without prejudice and substitute therefor new claims 39 - 82:

39. Fluid flow contouring apparatus for preferentially contouring the fluid path of a process fluid flowing cross-wise across and contacting a plurality of spaced-apart heat transfer conduits, said apparatus comprising a plurality of longitudinally continuous, sleeve-shaped baffle structures, each baffle structure comprising at least a paired set of fluid flow apertures which constitute the only upstream-to-downstream fluid passage through the fluid flow contouring apparatus, each of said baffle structures substantially symmetrically surrounding a heat transfer conduit to define an annular-shaped fluid flow region thereby isolating cross-wise fluid flow around that associated heat transfer conduit from cross-wise fluid flow around adjacent heat transfer conduits located transversely to the direction of fluid flow, and wherein the fluid flow apertures of a baffle structure are symmetrically located respectively upstream and downstream of the associated heat transfer conduit in at least partial upstream and downstream alignment with each other and with the associated heat transfer conduit, whereby each said baffle structure contours the flow path of said process fluid to establish a substantially uniform fluid flow pattern around the contour of the associated heat transfer conduit.